

SECTION 10 51 62**COMBINATION PADLOCKS****PART 1 - GENERAL****1.1 SUMMARY**

- A. Furnish Master Lock mechanical portable combination locks for installation on lockers, cabinets or containers as shown or indicated on approved drawings.

1.2 SUBMITTALS

- A. Provide in accordance with Section 01 33 00 - Submittal Procedures:
 - 1. Product data for locks.
- B. Provide in accordance with Section 01 78 00 - Closeout Submittals:
 - 1. Printed control chart and text file on disc of serial numbers and lock combinations.

PART 2 - PRODUCTS**2.1 ACCEPTABLE MANUFACTURERS**

- A. Master Lock Company, 6744 South Howell Ave, P.O. Box 927, Oak Creek, Wisconsin 53154; 800-308-9244; www.masterlock.com.
- B. Requests to use equivalent products of other manufacturers shall be submitted in accordance with Section 01 63 00 - Product Substitution Procedures.

2.2 GENERAL SECURITY PORTABLE COMBINATION PADLOCKS

Master Lock provides these 6 models of portable combination locks for padlock eye or hasp style lockers.

Edit the following to reflect required model:

- Model 1502: Padlock with 3/4 inch shackle.
- Model 1525: Padlock with 3/4 inch shackle and key supervisory access.
- Model 1502LF: Padlock with 1-1/2 inches shackle.
- Model 1525LF: Padlock with 1-1/2 inches shackle and key supervisory access.
- Model 1502LH: Padlock with 2 inches shackle.
- Model 1525LH: Padlock with 2 inches shackle and key supervisory access.
- Model 1572: Padlock with 3/4 inch shackle.
- Model 1585: Padlock with 3/4 inch shackle and key supervisory access.

Model 1572LF: Padlock with 1-1/2 inches shackle.

Model 1585LF: Padlock with 1-1/2 inches shackle and key supervisory access.

Model 1572LH: Padlock with 2 inches shackle.

Model 1585LH: Padlock with 3/4 inch shackle and key supervisory access.

- A. Type: General security, combination padlock.
- B. Construction: Double-reinforced stainless steel case with cold-rolled steel shielding locking mechanism from physical attack.
- C. Shackle: Hardened steel resistant to cutting and prying. Fits lockers with 5/16 inch minimum diameter padlock eye or hasp.
- D. Combination: 3 digits selected from 40 number dial.
- E. Operation:
 - 1. Dial automatically locks under shackle tension to prevent feeling out the combination.
 - 2. Combination automatically scrambles when lock is closed to prevent accidental opening.
- F. Provide 4 pin tumbler cylinder on backside of padlock for supervisory access.
- G. Provide custom designed padlock dials with:
 - Edit the following to reflect model*
 - 1. Integral color: [__color__] from manufacturer's standard range.
 - 2. Laser engraved text: [__text__].
 - 3. Custom logo: [__Image__].

PART 3 - EXECUTION

3.1 EXAMINATION:

- A. Examine areas and conditions in which the locks will be installed.

3.2 INSTALLATION:

- A. Locks shall be installed in accordance with lock manufacturer's instruction.

3.3 QUALITY ASSURANCE:

- A. Master Lock reserves the right to modify the design and/or function of lock and

change specifications to maintain compliance with corporate quality assurance polices.

END OF SECTION