

Drop Slot Safe

Thank you for purchasing this security safe from Sentry®Safe. This guide is designed to maximize the user and security features of this project.

1 Operating instructions

To open the safe:

1. Insert key labeled 'A' into bottom lock; turn counter-clockwise to 9 o'clock
2. Insert numerically labeled key into top lock; turn clockwise to 5 o'clock
3. Slowly pull door towards you

2 Bolt-down instructions

This kit contains:

- Four (4) Masonry Anchors

Required tools:

- Powered Drill
- Adjustable Wrench
- 1/2 in. (M12) Masonry Drill

Instructions:

1. Unlock safe and open door.
2. Remove safe floor carpet.
3. Look on the bottom of safe for four (4) holes with cap plugs.

4. Remove the cap plugs.
5. Position the safe in the desired location.
6. From inside the safe mark the location of the four (4) bolt down holes.
7. Move the safe aside to the clear marked spots for drilling.
8. Using the 1/2 in. masonry drill, drill a 4 in. deep hole in the marked locations.
9. Replace the safe in the desired location with the holes in the safe aligned with the drilled holes in the floor.

10. Pass each masonry anchor through the safe floor into the drilled holes; making contact with the safe floor.
11. Tighten each masonry anchor with the adjustable wrench.
12. Replace safe floor carpet.

3 Replacement keys

To obtain replacement keys, locate the serial number of the unit on a small label on the right side of the safe (outside). Send a copy of this number, a notarized letter (last name of notary must be different than that of the owner) stating that you are the owner of

the safe, and a check or money order (U.S. funds) for \$30.00 to: Sentry Group, Dept. 200, 882 Linden Avenue, Rochester, NY 14625-2784 USA. If you need assistance in preparing your order, or wish to purchase via credit card (Visa/Mastercard only),

please call Sentry Customer Service toll-free Monday-Friday (8:00am - 6:00pm E.S.T.) at 1-800-828-1438. Prices subject to change without prior notification.